

NITROSource Plus - NSP-040



PSA Nitrogen Gas Generator

Nitrogen Outlet Flow Rates

Inlet Pressure		Purity (Remaining Oxygen Content) vs Nitrogen Outlet Flow (m ³ /hr)*										
bar(g)	psi(g)	5ppm	10ppm	50ppm	100ppm	250ppm	500ppm	0.1%	0.5%	1.0%	2.0%	3.0%
5.0	72.5	7.4	8.5	12.6	14.4	17.0	20.0	22.3	31.0	36.6	43.5	52.9
6.0	87.0	9.9	11.3	16.1	18.4	21.8	25.5	28.5	38.4	45.3	53.9	63.1
7.0	101.5	12.5	14.4	19.4	22.1	26.2	30.8	34.4	46.3	54.6	64.9	73.4
8.0	116.0	14.4	16.5	21.8	24.8	29.4	34.5	38.5	51.4	59.5	70.7	80.0
9.0	130.5	16.3	18.7	24.1	27.4	32.5	38.1	42.6	56.5	64.9	77.2	87.4
10.0	145.0	18.1	20.8	26.6	30.3	35.9	42.1	47.1	61.1	69.8	83.1	94.0
11.0	159.5	19.3	22.1	27.6	31.4	37.2	43.7	48.8	63.9	72.6	86.3	97.7
12.0	174.0	20.4	23.4	28.8	32.8	38.8	45.5	50.9	66.2	75.3	89.5	101.3
13.0	188.5	21.5	24.7	29.7	33.9	40.1	47.1	52.6	69.0	77.5	92.1	104.3

Performance data is based on 7.0 bar(g) (101.5 psi(g)) inlet and 20°C (68°F) ambient temperature.

*m³ reference to standard conditions, 20°C, 1013 mbar(a) and 0% relative water vapour pressure.

Part Number Breakdown

		N	S	P	-	0	4	0	-							-	0	0	A
Purity	Prefix																		
5ppm / 10ppm / 50ppm	U																		
100ppm / 250ppm / 500ppm / 0.1%	H																		
0.5% / 1.0% / 2.0% / 3.0%	L																		
Oxygen Analyser Technology	Prefix																		
Electrochemical	E																		
Zirconia	Z																		
Energy Saving Technology ⁽¹⁾	Prefix																		
Not Fitted	N																		
Fitted	Y																		
Nitrogen Outlet Flow Range ⁽²⁾	Prefix																		
High Flow	H																		
Low Flow	L																		
Dew point Monitoring	Prefix																		
Not Fitted	N																		
Inlet PDP Monitoring	I																		
Outlet PDP Monitoring	O																		
Both Inlet & Outlet Monitoring	B																		

⁽¹⁾ Energy Saving Technology not available on 50ppm, 10ppm or 5ppm generators.

⁽²⁾ See 'Mass Flow Controller Flow Breaks' chart for sizing information.

Mass Flow Controller Flow Breaks

Outlet Pressure	bar(g)	5	6	7	8	9	10	11	12	13
	psi(g)	72.5	87	101.5	116	130.5	145	159.5	174	188.5
High Flow	m ³ /hr*	190.0	205.0	219.0	232.0	245.0	257.0	268.0	279.0	290.0
Low Flow		61.0	66.0	70.0	74.0	78.0	82.0	86.0	89.0	93.0

*m³ reference to standard conditions, 20°C, 1013 mbar(a) and 0% relative water vapour pressure.

Operation Parameters

Minimum Inlet Air Quality	ISO 8573-1: 2010 Class 2.4.1	
Minimum Operating Pressure	5.0 bar(g)	72.5 psi(g)
Maximum Operating Pressure	13.0 bar(g)	188.5 psi(g)
Design Pressure	15.0 bar(g)	217.5 psi(g)
Minimum Operating Temperature	5.0°C	41.0°F
Maximum Operating Temperature	50.0°C	122.0°F
Recommended Operating Temperature	20.0°C	68.0°F
Supply Voltage	100-240V AC (±10%) 50/60Hz	
Power Consumption	100W	
IP Rating	IP32	NEMA 2
Noise	<75 dB (A)	


Pipe Connections & Buffer Vessel Sizes

Model	Pipe Connections				Buffer Vessel	
	Compressed Air Inlet	Nitrogen Outlet	To Buffer	From Buffer	Minimum* Capacity	
NSP-040	1" BSPP	1" BSPP	1" BSPP	1" BSPP	500 Litres	132 Gallon

***Important Note:**
Recommended minimum buffer vessel size to guarantee maximum outlet pressure.
Utilisation of smaller buffer vessels may result in lower outlet pressures and fluctuations in purity.

Weights & Dimensions

Height (H)	2063mm	81.2"
Width (W)	550mm	21.7"
Depth (D)	1221mm	48.1"
Weight	522 kg	1151 lbs





EMEA Product Information Centre
Free phone: 00 800 27 27 5374
(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre
Toll-free number: 1-800-27 27 537
www.parker.com/gsfe